



USA | UPPAbaby, 276 Weymouth Street, Rockland, MA 02370

Canada | UPPAbaby Canada, 201 Wicksteed Avenue, Suite 2, Toronto, Ontario M4G 0B1

uppababy.com | 1.844.823.3132


Model 1002-MSA-CA

All rights reserved. © 2024 UPPAbaby. UPPAbaby and all associated logos are trademarks. All product specifications are correct at time of print. UPPAbaby reserves the right to change anything at any time without prior notice. Color representation is as close as print processes allow. Not all colors available at all retailers. UbMAN099-V13

UPPAbaby[®] MESA[®] **V2**



From 1.8-15.9 kg
(4-35 lbs)



WELCOME TO THE FAMILY

We are with you for the long haul. Register your car seat
within three months to claim your

Limited Lifetime Warranty.*

Thank you for being part of the UPPAbaby family.



*Lifetime warranty applies to UPPAbaby car seats and the original owner, within the lifetime of the product. To receive your Limited Lifetime Warranty, you MUST register within three months of purchase and provide a valid purchase receipt from an authorized UPPAbaby retailer. The "lifetime" of the product is defined as the period of use by the registrant for use with his/her children up to 7 years from date of manufacture. For complete UPPAbaby Warranty refer to page 71.

For replacement parts, service or additional questions, please contact our Customer Experience Team:
uppababy.com/support | email: support@uppababy.com | 844-823-3132

Before You Begin	4	Base Installation With Lower Anchors	26	Carrier Installation with Vehicle Seat Belt	42	Stroller Compatibility	62
Registration	4	Leveling the Base	26	Determining Best Installation Method	42	Fitting Carrier to Stroller Frame	62
Certification	4	Base Installation With Lower Anchors	27	Leveling the Carrier	43	Releasing Carrier from Stroller Frame	63
Child Use Recommendations	5	What is a Waterfall?	28	Lap/Shoulder Belt Preferred Routing Method	44		
Notice of Expiration	6	Safety Check	30	Lap/Shoulder Belt Optional Routing Method	46	Care + Maintenance	64
		Uninstalling the Base	31	Lap Belt Only Routing Method	48	Cleaning	64
Warnings + General Safety Instructions	7			Installation with Locking Clip	49	SIP Padding Removal	65
		Base Installation With Vehicle Seat Belt	32	Safety Check	50	Seat Padding Removal	66
Features Overview	16	Leveling the Base	32	Aircraft Installation	51	Seat Padding Installation	68
Overview of Base	16	Lap/Shoulder Belt Routing Method	34			SIP Padding Installation	70
Overview of Carrier	18	Lap Belt Only Belt Routing Method	36	General Use	52		
		What is a Waterfall?	38	SIP Carriage + Harness Positioning	52	Warranty	71
Vehicle Compatibility	20	Safety Check	40	Securing Your Child	53		
Choosing A Vehicle Seating Location	20	Uninstalling the Base	41	Crotch Belt Positions	55		
Determining Best Installation Method	21			Infant Insert	56		
UAS (Universal Anchorage System)	22			Attaching Carrier to Base	57		
Overview of Vehicle Seat Belt Systems	23			Releasing Carrier from Base	58		
Unsafe Vehicle Seat Belt Systems + Seating	24			Using Canopy	59		
				Using Carry Handle	60		
				Important Checks	61		

**READ ALL INSTRUCTIONS BEFORE USE
OF THIS CHILD RESTRAINT.**

KEEP THESE INSTRUCTIONS FOR FUTURE REFERENCE.

(Storage pocket located on underside of base.)

BEFORE YOU BEGIN

REGISTRATION

Model Name: **Mesa V2** Model Number: **1002-MSA-CA**
Serial Number: _____
Date of Purchase: _____

TAKE A MOMENT TO FILL OUT THE ABOVE INFORMATION.

Information can be found on the manufacture labels or engraved on the underside of the carrier.



Please register your child restraint by filling out and sending the postage-paid registration card that came with your child restraint OR register online at: uppababy.com/ca/register.

Child restraints can be recalled for a variety of safety reasons. **You must register this restraint to be reached in a recall.**

For recall information, call Transport Canada's Motor Vehicle Safety Centre at 1-800-333-0371 or go online to tc.gc.ca/eng/motorvehiclesafety/safedrivers-childdafety-notices-menu-907.htm.

CERTIFICATION



This child restraint system conforms to all applicable Canadian Motor Vehicle Restraint Systems and Booster Seat Safety Regulation (RSSR) and Canadian Motor Vehicle Safety Standard (CMVSS 213) for child restraint systems and (CMVSS 213.1) for infant restraint systems.



This child restraint is certified for aircraft use. UPPAbaby and Transport Canada Civil Aviation (TCCA) strongly urge you to secure your child in a child restraint system (CRS) or device for the duration of your flight.

BEFORE YOU BEGIN

CHILD USE RECOMMENDATIONS


Children should remain rear-facing for as long as possible.

UPPAbaby advises that all infants and toddlers should ride in a rear-facing car safety seat (CSS) as long as possible, until they reach the highest weight or height allowed by their CSS's manufacturer. This child restraint is for use by children who meet BOTH requirements below:


WEIGHT REQUIREMENTS: 1.8 – 15.9 kg (4 – 35 lbs)

HEIGHT REQUIREMENTS: 81.3 cm (32 in) or less


The Infant Insert is designed for children who weigh: **1.8 – 5 kg (4 – 11 lbs)**



The top of the child's head should not be less than 2.5 cm (1 in) from the top of the headrest when in its highest position.



Harness should be at the shoulders or slightly below.




Retainer clip must be at armpit level **1** and harness straps should be snug **2**.

BEFORE YOU BEGIN

NOTICE OF EXPIRATION

Discontinue use of this child restraint after 7 years from the date of manufacture or after a crash. Refer to labels on bottom of Carrier and Base.



WARNINGS + GENERAL SAFETY INFORMATION

WARNING

DEATH OR SERIOUS INJURY CAN OCCUR

Failure to follow these instructions and those appearing on the restraint system could result in serious injury to your child or other vehicle occupants. According to accident statistics, children are safer when properly restrained in the rear seating positions than in the front seating positions.

- **NEVER** leave Child Restraint unsecured in your vehicle even when it is unoccupied. In a crash, it could become a projectile and injure other vehicle occupants.
- Use only in rear-facing position when using it in the vehicle.

WARNINGS + GENERAL SAFETY INFORMATION




NEVER place this Child Restraint on a front seat with an airbag. **DEATH OR SERIOUS INJURY** can occur. An airbag can strike a rear-facing infant restraint with enough force to crack the shell and seriously injure or kill an infant.

The back seat is the safest place for children 12 and under. Refer to the vehicle owner's instruction book before installing this Child Restraint in a seating position with side airbags.

Snugly adjust the belts provided with this child restraint around your child. A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

WARNINGS + GENERAL SAFETY INFORMATION

WARNING



Children have **STRANGLED** in loose or partially buckled harness straps. Fully restrain the child even when carrier is used outside the vehicle.

SUFFOCATION HAZARD: Infant carrier can roll over on soft surfaces and suffocate child. **NEVER** place carrier on beds, sofas, or other soft surfaces.

- **NEVER** leave child in carrier when straps are loose or undone.
- **NEVER** place carrier near window where cords from blinds or drapes can strangle a child.

WARNINGS + GENERAL SAFETY INFORMATION

- **NEVER** hang strings on or over the carrier or attach to handle.
- **NEVER** place items with a string around a child's neck, such as hood strings, pacifier cords, etc.

FALL HAZARD: Child's movement can slide carrier.

- **NEVER** place carrier on counter tops, tables, or any other elevated surfaces. **DO NOT** use on shopping carts.
- **NEVER** leave child unattended.

WARNINGS + GENERAL SAFETY INFORMATION

WARNING



FALL HAZARD: The carrier can fall from the shopping cart.
DO NOT use on shopping cart.

SAFETY WARNINGS

Failure to follow these instructions could result in serious injury to your child or other vehicle occupants.

- **ALWAYS** keep child properly harnessed when child is in carrier.

WARNINGS + GENERAL SAFETY INFORMATION

- **DO NOT** remove or cover up any of the warning or product labels on this Child Restraint. All labels include information required by law.
- **DO NOT** lubricate buckles and fasteners.

AVOID BURN INJURY:

- **ALWAYS** check all surfaces of restraint before securing your child. In warm weather, child restraints can become very hot. Park in the shade or where sun does not directly hit the Child Restraint. Cover the Child Restraint with a sheet or blanket when not in use.

AVOID INJURY FROM FLYING OBJECTS IN A CRASH:

- **ALWAYS** properly store lower anchor connectors when not in use.
- **DO NOT** leave loose objects, e.g. cups, toys, bags, umbrellas, etc., in the vehicle because they can become deadly projectiles in a crash.

WARNINGS + GENERAL SAFETY INFORMATION

- Check the vehicle owner's manual for more information about airbag/child restraint use.
- **DO NOT** use the carrier or base if damaged or broken, expired (over 7 years from date of manufacture), missing instructions, missing parts, or if the straps are cut, frayed, or damaged in any way.
- **DO NOT** use this Child Restraint system if it has been in a vehicle accident.
- **DO NOT** use clothing or blankets that interfere with fastening or tightening the harness **INSTEAD** place a blanket over the child after being properly secured in the harness.
- **DO NOT** use this Child Restraint system if the top of the child's head is less than 2.5 cm (1 in) from the top of the headrest when in its highest position.

WARNINGS + GENERAL SAFETY INFORMATION


- **DO NOT** use this Child Restraint system in a vehicle seating position where it cannot be tightly secured.
- **DO NOT** install in rear-facing or side-facing vehicle seats.
- **DO NOT** modify this restraint except as instructed in this instruction book. Minor modifications can change the way a Child Restraint performs in a crash.
- **DO NOT** take child out of the Child Restraint while the vehicle is moving.
- **DO NOT** allow children to play with this Child Restraint. It is not a toy.
- **DO NOT** use any accessories, pads, or products supplied by other manufacturers with this Child Restraint, unless approved and tested by UPPAbaby. Items not tested with this restraint could injure your child.
- **DO NOT** use a Child Restraint with damaged or missing parts.

WARNINGS + GENERAL SAFETY INFORMATION

- **DO NOT** place carrier on top of shopping cart. Carrier will not be secure and could fall causing injury to child.
- **DO NOT** hang objects from Rear Vehicle Seat Belt Guide.
- **VEHICLE CLASSIFICATION:** This car seat is only for use in the following classification of vehicles: passenger cars, trucks and multi-purpose vehicles such as SUVs (sports utility vehicles) and CUVs (crossover utility vehicles).


FEATURES OVERVIEW – Overview of Base

- 1 Vehicle Belt Guides (2)
- 2 Lower Anchor Connector Release Buttons (2)
- 3 Level Adjust Button
- 4 Tightness Indicator
- 5 Lower Anchor Connectors
- 6 Lower Anchor Connector Webbing
- 7 Vehicle Belt Lock-Off (Closed)




FEATURES OVERVIEW – Overview of Base

- 8 Vehicle Belt Lock-Off (Open)
- 9 Level Angle Indicators (2)
- 10 Adjustment Foot
- 11 Lower Anchor Connector Storage
- 12 Instruction Manual Storage
- 13 Locking Clip




FEATURES OVERVIEW – Overview of Carrier

- 1 (SIP) Adjuster Tab
- 2 Side Impact Protection (SIP)
- 3 Harness Covers (2)
- 4 Buckle
- 5 Infant Insert
- 6 Harness Adjuster Release
- 7 Harness Adjuster Strap
- 8 Buckle Latch Plates (2)
- 9 Harness Holder Pockets (2)
- 10 Retainer Clip
- 11 Harness Straps
- 12 Canopy
- 13 Manufactured/Expiration Date
- 14 Harness Anchors (2)
- 15 Vehicle Seat Belt Guides (2)
- 16 Carrier Release From Base
- 17 Carrier Release From Stroller
- 18 Carry Handle Adjustment Buttons (2)
- 19 Stroller Attachment
- 20 Rear Vehicle Seat Belt Guide
- 21 Crotch Belt Positions



FEATURES OVERVIEW – Overview of Carrier



VEHICLE COMPATIBILITY – Choosing a Vehicle Seating Location


Please read the following information before installing this Child Restraint!

The safest seating position is one that works best for your specific car seat, family and vehicle. When determining whether the Mesa V2 rear-facing car seat can be used with lower anchors in the rear center seating position, it is critical that you refer to your vehicle owner's instruction book. If the Mesa V2 does not install best in the rear center seating location, it is recommended to move to one of the outboard seating positions.

Before installing this child restraint you must determine the method of installation and the best vehicle seating position for that method. This child restraint can be installed either using the **(UAS) Universal Anchorage System** or the **Vehicle Seat Belt**.



ALWAYS park on a level surface when installing a Child Restraint.



Vehicle Seat Belt Retractor

VEHICLE COMPATIBILITY – Determining Best Installation Method


At this point take out your VEHICLE OWNER'S INSTRUCTION BOOK. You will need this to look up different features in your vehicle that might affect the installation.

⚠ WARNING! NEVER place a rear-facing only child restraint in front of an active airbag.

BASE INSTALLATION



**(UAS)
Lower Anchor**
(pg 26)



Lap/Shoulder Belt
(pg 32)




**Lap/Shoulder Belt
Preferred Routing**
(pg 43)



**Lap/Shoulder Belt
Optional Routing**
(pg 43)



**Lap Belt Only
Routing**
(pg 43)



Lap Belt Only (pg 32)



NOTE: The carry handle must be locked in the (4th) rebound position when in use.




VEHICLE COMPATIBILITY

UAS (Universal Anchorage System)

Most vehicles manufactured after September 1, 2002 are equipped with **UAS (Universal Anchorage System)**. Check your vehicle owner's instruction book to determine lower anchor compatible seating positions.

NOTE: No tether is required with this rear-facing carrier. Only lower anchors are used.

NOTE: In order to use the rear center seating position with lower anchor, the distance between the lower anchors may be up to 55.9 cm (22 in) and the seating position must be approved by the vehicle manufacturer. If spacing between the lower anchors is greater than 55.9 cm (22 in) or if the seating position is not approved by the vehicle manufacturer then use the vehicle seat belt for installation.



VEHICLE COMPATIBILITY

Overview of Vehicle Seat Belt Systems





If you do not use lower anchor to properly secure the child restraint you must use the **VEHICLE SEAT BELT SYSTEM**. Seat belt systems vary by make, model, and year of your vehicle. There are some vehicle belts that will NOT work with this child restraint or that require additional steps.

CHECK YOUR VEHICLE OWNER'S INSTRUCTION BOOK for information regarding your vehicle seat belt system(s).

This child restraint is compatible with most vehicle seat belt systems


⚠ WARNING! Vehicle seat belts must stay tightly secured around the car seat at all times.



VEHICLE COMPATIBILITY – Unsafe Vehicle Seat Belt Systems + Seating

This Child Restraint can only be installed on vehicle seats that face forward.

DO NOT install in seats that face to the sides or rear of the vehicle.




⚠️ WARNING! DEATH OR SERIOUS INJURY CAN OCCUR.


CHECK YOUR Vehicle instruction book for information regarding your vehicle seat belt system(s). Not all vehicle seat belts work with this Child Restraint.

VEHICLE COMPATIBILITY – Unsafe Vehicle Seat Belt Systems + Seating


DO NOT use this Child Restraint with the following seat belt systems:



Lap belts with emergency locking retractor




Motorized (automatic)



Lap/Shoulder with two retractors



Door mounted



Inflatable



BASE INSTALLATION WITH LOWER ANCHORS

LEVELING THE BASE


- 1 Place the base on the vehicle seat with the adjustment foot toward the vehicle seat back.
- 2 Press the level adjust button on the top of the base to extend the foot and change the recline angle. Check the angle indicators on either side of the base. The base is level when only the **GREEN** marker is visible between the two arrows. No **RED** should be visible.




NOTE: Vehicle must be parked on a level surface to properly level the base.




If proper angle cannot be achieved with adjustable foot, a rolled towel may be used. Foot must be in fully extended position.



BASE INSTALLATION WITH LOWER ANCHORS



- 3 Locate the lower anchor connectors on either side of the base and remove by pushing the corresponding orange button on the top of the base **1** while pulling the connector out of the lower anchor storage pocket **2**.
 - 4 Attach the lower anchor connectors to the vehicle lower anchors located in the vehicle seat bight (crease of seat).
- NOTE:** Check lower anchor connectors are in the upright position.
- 5 Apply pressure firmly into the base allowing all the excess lower anchor connector webbing to retract and tighten.



Push into the seat bight (crease of seat). Installation is complete when tightness indicator turns from **RED** to **GREEN** and stays green when downward push is discontinued.


REVIEW SAFETY CHECK ON PAGE 30.
ALL STEPS MUST BE ACHIEVED.



BASE INSTALLATION WITH VEHICLE SEAT BELT


What is a Waterfall?

Many late model vehicles have what industry professionals call a waterfall. A waterfall is the wedge of material where your vehicle seat cushion and seat back meet. In some cases, this may interfere with the leveling foot on your UPPAbaby Mesa, preventing it from 'sitting' properly in the crease of the vehicle seat.



BASE INSTALLATION WITH VEHICLE SEAT BELT

What is a Waterfall?




This is an easy issue to resolve by following the steps below:

- 1 Uninstall your Mesa base.
- 2 Adjust the level adjustment foot to achieve proper recline level.
NOTE: The level angle indicator is located on either side of the Mesa base. It **MUST** be all **GREEN**. In cases where a waterfall is present, we recommend extending the foot to its **HIGHEST** position.
- 3 Push the base into the seat back. If there is a gap between the top of the Mesa base and the back of the vehicle seat, place a rolled hand towel in the gap flush with the top of the base.
- 4 Proceed to **BASE INSTALLATION WITH LOWER ANCHORS** (pg 27). Follow Safety Check (pg 30) to confirm proper installation.




BASE INSTALLATION WITH LOWER ANCHORS – Safety Check



Base doesn't more than 2.5 cm (1 in) side-to-side and front-to-back at the belt path.

Lower anchor connector webbing is secure and untwisted.





Ensure tightness indicator is **GREEN** after each use. If it is not, apply pressure by pushing base into seat bight (crease of seat) to tighten.



Recline angle is correct. Base is level when only **GREEN** is visible between the two arrows on the level indicator. No **RED** should be visible.

BASE INSTALLATION WITH LOWER ANCHORS



UNINSTALLING THE BASE

- 1 Press the **RED** button on the lower anchor connector while pulling the connector off the vehicle anchor.
- 2 Store lower anchor connectors in designated housing found on each side of the base.



BASE INSTALLATION WITH VEHICLE SEAT BELT

LEVELING THE BASE



- 1 Place the base on the vehicle seat with the adjustment foot toward the vehicle seat back.
- 2 Press the level adjust button on the top of the base to extend the foot and change the recline angle. Check the angle indicators on either side of the base. The base is level when only the **GREEN** marker is visible between the two arrows. No **RED** should be visible.



NOTE: Vehicle must be parked on a level surface to properly level the base.




If proper angle cannot be achieved with adjustable foot, a rolled towel may be used. Foot must be in fully extended position.




BASE INSTALLATION WITH VEHICLE SEAT BELT

PROCEED TO CHOSEN INSTALLATION METHOD:



**LAP/SHOULDER
ROUTING METHOD**
PAGE 34




**LAP BELT ONLY
ROUTING METHOD**
PAGE 36




BASE INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Belt Routing Method


1



2



3




- 1 Open lock-off.
- 2 Route the vehicle belt through the vehicle belt path while guiding the lap portion of the belt as close as possible to the top of the lock-off where the door hinges. Buckle the vehicle belt.
- 3 Hold shoulder portion of belt above base. With one hand, push down base in the direction of the seat bight (crease of seat) and hold firm as you pull shoulder belt.




BASE INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Belt Routing Method

4




5



- 4 While holding taut, slide shoulder belt back through the belt path as close as possible to the top of the lock-off.

NOTE: Tightness indicator should be **GREEN**.



- 5 Close the top section of the lock-off over the lap/shoulder belt 1. Second, close the bottom section of the lock-off over the belt 2. Make sure you push the bottom of the lock-off all the way down until you hear an audible click.



REVIEW SAFETY CHECK ON PAGE 40.
ALL STEPS MUST BE ACHIEVED.



BASE INSTALLATION WITH VEHICLE SEAT BELT

Lap Belt Only Routing Method

- 1 Open lock-off.
- 2 Route the vehicle belt through the belt path while guiding the lap portion of the belt as close as possible to the topside of the lock-off where the door hinges. Buckle the vehicle.




BASE INSTALLATION WITH VEHICLE SEAT BELT

Lap Belt Only Routing Method



- 3 With one hand push down base and hold firm as you pull lap belt to tighten and remove any slack.

NOTE: Tightness indicator should be **GREEN**.



- 4 Close the top section of the lock-off over the belt then close the bottom section of the lock-off over the belt. Make sure you push the bottom of the lock-off all the way down until you hear an audible click.

NOTE: Before closing the lock-off door, make sure the vehicle seat belt has not slipped down into the belt path and is as close as possible to the topside of the lock-off where the door hinges.




REVIEW SAFETY CHECK ON PAGE 40.
ALL STEPS MUST BE ACHIEVED.



BASE INSTALLATION WITH VEHICLE SEAT BELT


What is a Waterfall?

Many late model vehicles have what industry professionals call a waterfall. A waterfall is the wedge of material where your vehicle seat cushion and seat back meet. In some cases, this may interfere with the leveling foot on your UPPAbaby Mesa, preventing it from 'sitting' properly in the crease of the vehicle seat.



BASE INSTALLATION WITH VEHICLE SEAT BELT

What is a Waterfall?




This is an easy issue to resolve by following the steps below:

- 1 Uninstall your Mesa base.
- 2 Adjust the level adjustment foot to achieve proper recline level.
NOTE: The level angle indicators are located on either side of the base and bubble must be within the lines. In cases where a waterfall is present, we recommend extending the foot to its HIGHEST position.
- 3 Push the base into the seat back. If there is a gap between the top of the Mesa base and the back of the vehicle seat, place a rolled hand towel in the gap flush with the top of the base.
- 4 Proceed to **BASE INSTALLATION WITH VEHICLE SEAT BELT** (pg 34 or 36) based on your method of installation). Follow Safety Check (pg 40) to confirm proper installation.



BASE INSTALLATION WITH VEHICLE SEAT BELT

Safety Check



Lock-off must be used at all times when installing with a vehicle seat belt.

Vehicle Belt is secure and untwisted.

Base doesn't more than 2.5 cm (1 in) side-to-side and front-to-back at the belt path.




Ensure tightness indicator is **GREEN** after each use. If it is not, reinstall base.



Recline angle is correct. Base is level when only **GREEN** is visible between the two arrows on the level indicator. No **RED** should be visible.

BASE INSTALLATION WITH VEHICLE SEAT BELT



UNINSTALLING THE BASE


- 1 Unbuckle seat belt.
- 2 Open lock-off.
- 3 Remove seat belt.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

DETERMINING BEST INSTALLATION METHOD

There are (3) methods of carrier only installation:



LAP/SHOULDER PREFERRED ROUTING METHOD

Installation with both the lap and shoulder belt.

PAGE 44



LAP/SHOULDER OPTIONAL ROUTING METHOD

Installation with both the lap and shoulder belt.

PAGE 46



LAP BELT ONLY ROUTING METHOD


No shoulder belt is used. This method applies to vehicle with no shoulder belt and aircraft.

PAGE 48



CARRIER INSTALLATION WITH VEHICLE SEAT BELT


1



LEVELING THE CARRIER

- 1 Place the carrier rear-facing on the vehicle seat.
- 2 Make sure the vehicle is parked on level ground and the **RED** line on the carrier is level to the vehicle floor.

2



For a more stable installation, a rolled towel may be used.




CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Belt Preferred Routing Method

If shoulder belt does not route around the back of the Mesa V2 carrier, follow
LAP/SHOULDER BELT OPTIONAL ROUTING METHOD PAGE 46

- 1 Route the lap portion of the seat belt through both lap belt guides on the carrier and buckle the seat belt.
- 2 Route belt around the seat back through the rear belt guide.




⚠️ WARNING! Vehicle seat belt must lock, otherwise locking clip must be used. See page 49 for instructions.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Belt Preferred Routing Method



- 3 Lock vehicle seat belt.
NOTE: See vehicle owner's instruction book for more information on locking your seat belt for child restraint installations.
- 4 Push the carrier into the vehicle seat bight (crease of the seat) and gently apply pressure from behind the carrier into the vehicle seat back. At the same time, pull on the shoulder portion of the vehicle belt closest to the buckle and hold tightly.
NOTE: Be mindful of canopy.
- 5 Feed excess webbing into the vehicle retractor.
- 6 Rotate carry handle forward to the (4th) rebound position when in use.
NOTE: Check that the carrier is still properly leveled.



REVIEW SAFETY CHECK ON PAGE 50.
ALL STEPS MUST BE ACHIEVED.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Optional Routing Method

- 1 Route the lap portion of the seat belt through both lap belt guides on the carrier and buckle the seat belt.
- 2 Lock vehicle seat belt.
NOTE: See vehicle owner's instruction book for more information on locking your seat belt for child restraint installations.
- 3 Push the carrier into the vehicle seat bight (crease of the seat) and gently apply pressure from behind the carrier into the vehicle seat back. At the same time, pull on the shoulder portion of the vehicle belt closet to the buckle and hold tightly.
NOTE: Be mindful of canopy.




⚠ WARNING! Vehicle seat belt must lock, otherwise locking clip must be used. See page 49 for instructions.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Lap/Shoulder Optional Routing Method




- 4 Feed excess webbing into the vehicle retractor.
 - 5 Rotate carry handle forward to the (4th) rebound position when in use.
- NOTE:** Check that the carrier is still properly leveled.

REVIEW SAFETY CHECK ON PAGE 50.
ALL STEPS MUST BE ACHIEVED.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Lap Belt Only Routing Method



- 1 Route the lap belt through both guides on the carrier and buckle the seat belt.
- 2 Push the carrier into the vehicle seat bight (crease of the seat) and gently apply pressure from behind the carrier into the vehicle seat back. At the same time, pull on the looser portion of the lap belt closest to the buckle and hold tightly.

NOTE: Be mindful of canopy.

- 3 Rotate carry handle forward to the (4th) rebound position when in use.

NOTE: Check that the carrier is still properly leveled.


⚠ WARNING! DO NOT use lap belts with emergency locking retractor systems.

**REVIEW SAFETY CHECK
ON PAGE 50.
ALL STEPS MUST BE ACHIEVED.**



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

The locking clip can be found on the underside of the base (page 17). The locking clip can be used for **CARRIER** installation with Lap/Shoulder belt combination when the seat belt does not lock.




INSTALLATION WITH LOCKING CLIP

- 1 While pushing into the child restraint, pull the seat belt tight to eliminate any slack then pinch both pieces of seat belt webbing directly behind the latch plate. Unbuckle the belt without letting the webbing slip.
- 2 Thread the locking clip onto both lap and shoulder belts 2.5 cm (1 in) from the latch plate.
- 3 Re-buckle the vehicle belt.




CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Safety Check



Carrier doesn't move more than 2.5 cm (1 in) side to side and more than 2.5 cm (1 in) front-to-back at the belt path.

Vehicle belt is secure and untwisted.



Angle is correct when The **RED** line on the carrier is level with the vehicle floor.

Seating position is permitted by both UPPAbaby and your vehicle manufacturer for use with the type of Vehicle Seat Belt.



The carry handle must be locked in the (4th) rebound position when in use.



CARRIER INSTALLATION WITH VEHICLE SEAT BELT

Aircraft Installation



THIS CHILD SEAT IS CERTIFIED FOR AIRCRAFT USE WHEN USED WITHOUT A BASE.

UPPABABY AND TRANSPORT CANADA CIVIL AVIATION (TCCA) STRONGLY RECOMMEND THAT CHILDREN UP TO 18 KG (40 LBS) USE A CERTIFIED HARNESS CHILD RESTRAINT OR OTHER DEVICE APPROVED FOR AIRCRAFT TRAVEL.

AIRCRAFT INSTALLATION:

When installing this child restraint on an airplane, install the same way as **CARRIER INSTALLATION WITH VEHICLE SEAT BELT/LAP BELT ONLY ROUTING METHOD** (page 48).

NOTE: Make sure that the aircraft buckle does not interfere with the belt guides on the infant carrier.


⚠ WARNING! DO NOT use base with aircraft installation. Only the carrier is certified for aircraft use. Inflatable seat belts are not compatible with this child restraint.

SAFETY REMINDERS AND TIPS


- Notify the airline ahead of time that you'll be traveling with a child restraint.
- Install this carrier in a window seat to avoid blocking the aisle.
- Ask for a seat belt extender if the lap belt is too short.
- Use only on a forward-facing aircraft seat.
- DO NOT use this restraint if a secure installation cannot be achieved.
- Place carry handle in any of the (4) locked positions for use in the aircraft as long as it doesn't interfere with the back of the seat in front of the carrier.

GENERAL USE— SIP Carriage + Harness Positioning

This child restraint has an adjustable head restraint and no-retchard harness system that is easy to adjust to properly secure the child.



- 1 Adjust the head restraint by pulling on the adjuster tab **1** and sliding the head restraint up or down **2**.
- 2 Position the head restraint so the harness rests at the child's shoulders or slightly below.



GENERAL USE – Securing Your Child



- 1 Loosen the harness by pressing on the harness adjuster release button and pulling out the shoulder straps.
- 2 Open the retainer clip, unbuckle the harness, and tuck the latch plates into the side pockets to hold harness open.
- 3 Place infant in child restraint making sure their body is making full contact with the seating surface. Place harness over child and insert buckle tongues into the buckle until a “click” is heard. Pull up on the buckle tongues to make sure they are locked.

NOTE: See page 55 on crotch belt positions. The child should not be sitting on top of the buckle.



⚠ WARNING! NEVER use non-regulated products with this child restraint, unless approved by UPPAbaby.

STRANGULATION HAZARD: Children have strangled in loose or partially buckled harness straps. Fully restrain the child even when carrier is used outside the vehicle.

GENERAL USE – Securing Your Child



- 4 Pull up on the harness to remove excess slack around the child's legs.
- 5 Pull the harness adjuster strap to snugly adjust the harness straps around your child.
- 6 Close retainer clip and position at armpit level. Make sure the shoulder pads don't interfere with positioning the chest clip.

NOTE: See page 55 on crotch belt positions. The child should not be sitting on top of the buckle.









HARNESS SHOULD BE SNUG.

Pinch harness webbing at child's shoulders. If you can pinch webbing, the harness is too loose and should be tightened. For smaller babies, it is recommended to remove the harness pads for a more secure fit.

GENERAL USE – Crotch Belt Positions

The crotch belt and buckle has two use positions. Always position the buckle and crotch strap in the slot closest to the child. If the child is on top of the buckle in the inner position, then adjust the buckle to the outer position.




- 1 Unbuckle the harness.
- 2 Flip carrier over, insert the metal clip completely through the shell and seat pad.
- 3 Locate the appropriate buckle slot and insert from the top completely through the slot on the seat pad and shell.
- 4 Check that buckle is securely attached by pulling up on buckle.

GENERAL USE – Infant Insert

To ensure a better fit for smaller infants, the infant insert is recommended between **1.8 and 5 kg (4 and 11 lbs)**.

This Infant Insert was designed to optimize fit and body positioning for your child. When you can achieve all fit criteria without the insert, it can be removed.

NOTE: You may continue use beyond 5 kg (11 lbs) until all criteria are being met.



- 1 Harness straps are at or slightly below shoulders
NOTE: Harness pads are optional. They must be removed when securing a preemie
- 2 Chest clip is at armpit level
- 3 Crotch buckle rests securely against child with no gaps and child is not sitting on top of the buckle
NOTE: Crotch buckle pad is optional.
- 4 Room to tighten harness properly
- 5 Child is not slouching

NEVER use non-regulated products with this child restraint, unless approved by UPPAbaby.

GENERAL USE – Attaching Carrier to Base


- 1 Place carrier on base until a click is heard.
- 2 Check for a secure connection by pulling up on carry handle.




Carry handle must be locked in the (4th) rebound position when in use in the vehicle.




After attaching carrier to base check that the base is level. Base is level when only **GREEN** is visible between the two arrows on the level indicator.



GENERAL USE – Releasing Carrier from Base



- 1 Pull and hold carrier release button on back of the carrier.
- 2 Lift carrier off base.



Move carry handle to the (3rd) carry position before removing carrier from vehicle.

GENERAL USE – Using Canopy


Canopy easily adjusts to one of three (3) positions.

TO EXTEND CANOPY

Slowly pull forward on main canopy frame until resting in desired position.



TO RETRACT/STOW CANOPY

Gently push downward on main canopy frame allowing the center support and canopy fabric to guide into the storage compartment in carrier.



GENERAL USE— Using Carry Handle



To adjust the carry handle position, squeeze both handle adjustment buttons and rotate forward or backward.



The carry handle must be locked in any four (4) positions when in use: stand ①, store ②, carry ③ and rebound (vehicle use) ④.

⚠ WARNING! NEVER hang toys and other objects from the carry handle when using in the vehicle. These products have not been tested by UPPAbaby and therefore are not approved for use with this child restraint.

GENERAL USE – Important Checks




- This child restraint is for rear-facing use only.
- The seat must be tightly installed in a forward-facing vehicle seat.
- The harness should be at the shoulders or slightly below **A**.
- Retainer clip must be at armpit level and harness straps should be snug **B**.
- The top of child's head should not be less than 1 in from the top of the headrest when in its highest position.
- The child must weigh between 1.8 – 15.9 kg (4 and 35 pounds) and be no taller than 81.2 cm (32 in).
- The back seat is the safest place for children aged 12 and under.
- **NEVER** use non-regulated products with this child restraint, unless approved by UPPAbaby.
- **NEVER** place in front of an active airbag.
- Install using lower anchor or the vehicle seat belt, **NOT BOTH**.
- **DO NOT** secure an infant in the carrier with extra material, bulky clothing, or extra padding. Instead place a blanket over the harness after properly securing the child **C**.
- Carry handle must be locked in any of the (4) handle positions outside of the vehicle. While in the vehicle, the carry handle must be in the (4th) rebound position.
- Adjust base to the appropriate angle by using the grey button on top between the two orange buttons. The angle indicator on the sides of the base should be green, or the level line on the carrier should be level to the ground
- Always check the tightness indicator is green after each use.
- Always secure an unoccupied child restraint; in a crash an unsecured infant car seat may injure occupants in your vehicle.

STROLLER COMPATIBILITY – Fitting Carrier to Stroller Frame

Prior to fitting Mesa V2 carrier to stroller frame, engage brake on stroller and remove toddler seat from frame.

- 1 With carrier facing stroller handle, align carrier handle hubs with attachment posts on stroller.
- 2 Let carrier slide onto attachment posts. An audible click indicates proper attachment.
- 3 Lift up on car seat handle to check attachment.




COMPATIBLE WITH:

Vista V2, Vista 2015+, Cruz V2, Cruz
Compatible with Ridge and Minu strollers with use of adapters specific to each model.

STROLLER COMPATIBILITY – Releasing Carrier from Stroller Frame

- 1 Engage and hold the stroller release button on the top of the carry handle.
- 2 Lift the carrier off stroller frame.



CARE + MAINTENANCE – Cleaning

CLEANING FABRICS - Fabrics include: seat pad, infant inserts, buckle pads and shoulder pad.



Machine wash in cold water on gentle cycle with mild detergent. **DO NOT** bleach.



Dry flat and away from direct sunlight before re-use or storage.



DO NOT iron or dry clean.

CLEANING HARNESS WEBBING + CANOPY



Spot clean using warm water with mild detergent. **DO NOT** bleach.



Air dry completely before re-use or storage.

CLEANING PLASTIC



Spot clean using warm water with mild detergent. **DO NOT** bleach.




Towel dry completely before re-use or storage.

CLEANING BUCKLE AND LOWER ANCHOR CONNECTOR HARDWARE - Buckle should fasten with a “click”. If not, rinse under warm running water. **DO NOT** use detergents or lubricants.

CARE + MAINTENANCE – SIP Padding Removal

Following are fabric removal instructions for cleaning.




- 1 Unbuckle retainer clip and harness.
- 2 Pull forward on SIP padding releasing harness straps.
- 3 Pull SIP padding down from bottom and release.

CARE + MAINTENANCE – Seat Padding Removal




CARE + MAINTENANCE – Seat Padding Removal


- 5 Slide SIP to lowest position and release (8) plastic tabs from upper portion of carrier.
- 6 Thread SIP adjuster tab through buttonhole in top of seat pad.
- 7 Pull seat padding up and forward to remove padding around SIP.



CARE + MAINTENANCE – Seat Padding Installation



- 1 With the SIP in the lowest position, lay seat pad over carrier, open Velcro® flap and fit opening around SIP/headrest.
- 2 Tuck lowest side tab behind seat foam and under post. Repeat on other side.
- 3 Place second side tab into designated plastic slot and third side tab behind seat foam. Repeat on other side.
- 4 Tuck top 2 tabs into designated slots and pull headrest adjuster tab through buttonhole
- 5 Lift lower part of SIP and pull harness straps to each side of opening. Secure padding panel with Velcro®.






CARE + MAINTENANCE – Seat Padding Installation



- 6 Raise SIP/headrest into highest position.
- 7 Pull harness adjuster strap through opening in seat pad and install pad around adjuster release button housing.
- 8 Wrap padding around front lip and install 4 lower plastic tabs.



CARE + MAINTENANCE – SIP Padding Installation



- 1 Insert lower part of SIP carriage into pocket on the back of SIP padding.
- 2 Guide harness straps back into slots in SIP padding.
- 3 Secure SIP cover tightly around SIP ears.

WARRANTY



Welcome to the UPPAbaby family! We are with you for the long haul. Register your car seat within three months to claim your Limited Lifetime Warranty*.

Register your product at: uppababy.com/ca/register

*Lifetime warranty applies to UPPAbaby car seats and only the original owner, within the lifetime of the product. To receive your Limited Lifetime Warranty, you **MUST** register your car seat within three months of purchase and provide a valid purchase receipt from an authorized UPPAbaby retailer. The "lifetime" of the product is defined as the period of use by the registrant for use with his/her children up to 7 years from date of manufacture.

Your UPPAbaby product is warranted to be free from any manufacturing defects for a period of 2 years from the date of purchase under normal use and in compliance with the operating instructions.

This warranty is not transferable and extends only to the original retail purchaser and is only valid when supplied with proof of purchase from an authorized retailer. Proof of purchase must be retained for this warranty.

The warranty is valid only in the original country of purchase. This warranty is subject to the conditions set forth by country in which the items were purchased. Conditions may vary. UPPAbaby will not ship replacement or repair parts out of the country of purchase.

UPPAbaby will provide replacement parts or conduct repairs as determined fitting by the company. UPPAbaby reserves the right to exchange item with a replacement part. Some parts may be replaced with newer model parts as the product is improved over time.

WARRANTY

This warranty does not cover:

- Defects caused by misuse or poor maintenance. (Please refer to the product instruction booklet for guidance on item use and maintenance).
- Damage caused by improper installation of UPPAbaby parts and/or accessories. (Please refer to product instruction booklet for guidance on item assembly and use).
- Damage caused by corrosion mold or rust due to poor maintenance, service or storage.
- Damage resulting from normal wear and tear.
- Damage or degradation caused by the sun, sweat, detergents, damp storage conditions or frequent washings.
- Repairs or modifications carried out by a third party.
- Product purchased from an unauthorized retailer. (Approved retailers are listed on our website uppababy.com).
- Second owners and users other than the registrant.
- Damage resulting from airline shipping and handling.
- Products Involved in an accident.

UPPAbaby reserves the right to determine if warranty terms and conditions have been met.

For warranty service: In the US* and CA please contact UPPAbaby customer service (844) 823-3132 and visit uppababy.com/support to send an email.